

ECOTHOR™-16R

Contaminants	Removal	Best Results
Total Phosphorus	98.7%	0.02 mg/L
Ammonia Nitrogen*	92%	8 mg/L
FOGs	99.7%	0.7 mg/L
Heavy Metals	96%	0.007 mg/L
TSS	99.5%	4 mg/L
Coliforms	99.99%	<10 UFC/100 ml

*Simultaneous reduction of ammonia nitrogen and of phosphorus (Strutive).

BENEFITS

- No use of chemicals
- Compact & Modular Skids (containerized WWT)
- Fully Automated & Remote Monitoring
- Low Maintenance & Minimal Operator Attention
- Sludge Minimization & Stabilization
- Enables Nutrient Removal and Recovery
- Reduces greenhouse gas emissions compared to conventional coagulation-flocculation practices

AVAILABLE OPTIONS

Liquid-Solid Separation Equipment optimized for settling and/or flotation, and followed by filtration whenever needed.



3905 Lesage Street
Sherbrooke (Quebec) J1L 2Z9 Canada
info@e2metrix.com

www.e2metrix.com



E2Metrix Inc. specializes in providing innovative and clean electrolytic treatment solutions using ECOTHOR™, a series of electro-technology reactor models designed for Nutrient Removal, as well as other wastewater treatment applications requiring the removal of FOGs, Heavy Metals, TSS, and even Coliforms.

SYSTEM CAPABILITIES

- Exceptional Phosphorous Removal Performance (0 Phosphorous Target)
- Removal of Ammonia Nitrogen through struvite precipitation (patented process)
- Removal of complex organics (e.g.: Ethylene Glycol, Fluoride, PAHs)
- Can be used to target multiple contaminants simultaneously
- Removal of various pathogens

ECOTHOR™-16R

0-500 m³/d

